

# 휴대용 가스 측정기

(Handheld Gas Detector)



## 특징

- Auto Zeroing
- 실시간 연속측정
- 빠른 응답시간
- Filter 내장
- NDIR 센서채용
- 충전배터리(10 times)
- 소형,간편조작

Model	CH4 JHB	CO2 RHP	CO TDB	H2S LDB
Method	NDIR	NDIR	Electrochemical Sensor	Electrochemical Sensor
Range	0.5%/100% 선택	0~5000ppm/10% Dual Range	0~500ppm	0~100ppm
Resolution	0.01	1	1	1
Max Error	≤ ±3% FS	≤ ±3% FS	≤ ±3% FS	≤ ±3% FS
Drift	≤ ±1% /month	≤ ±1% /month	≤ ±1% /month	≤ ±1% /month
Display	3 disit	3 disit	3 disit	3 disit
예열시간	30 sec	30 sec	30 sec	30 sec
응답시간	25 sec	25 sec	25 sec	25 sec
Zeroing	Air Auto Zero	Air Auto Zero		
경보설정	Low High Alarm user setup	Low High Alarm user setup	Low High Alarm user setup	Low High Alarm user setup
Sampling	Diffusion	Diffusion	Diffusion	Diffusion
Dust Filter	5μm	5μm	5μm	5μm
전원	DC3.7V 리튬이온 충전배터리	DC3.7V 리튬이온 충전배터리	DC3.7V 리튬이온 충전배터리	DC3.7V 리튬이온 충전배터리
동작습도	0%~95% RH	0%~95% RH	0%~95% RH	0%~95% RH
동작온도	0~40%	0~40%	0~40%	0~40%
규격	93X62X25mm	93X62X25mm	93X62X25mm	93X62X25mm
중량	150g	150g	150g	150g